



Designation IEC:	HR14
Size:.....	C
Nominal Voltage:.....	1.2 V
Rated Capacity:.....	3000 mAh
Internal Resistance DC; fully charged:.....	40 mΩ
Impedance AC at 1 kHz; fully charged:.....	25 mΩ
Max. Discharge Current (continuous load / 0.8 V):.....	6.0 A

Typical Capacity at:	
0.2 C / 1.0 V:.....	3000 mAh
1.0 C / 0.9 V:.....	2700 mAh

Charge Retention:
 75 % of initial capacity after one year storage at 20 °C;
 determined at 0.2 C discharge rate

Dimensions:	
Diameter a:.....	26.2^{-1.3} mm
Height b:.....	50.0^{-1.4} mm
Shoulder Height c:.....	48.5^{-1.4} mm
Cap Diameter d:.....	7.5^{-2.0} mm
Volume:.....	26 cm³
Weight (approx.):.....	64 g

Charge Conditions at:	
Standard Charge:.....	300 mA, 16 h
Fast Charge:.....	3000 mA (-dV)
Trickle Charge (0.03 - 0.05 C):.....	90 - 150 mA

Temperatures (recommended / permissible) at:	
Storage:.....	-20 °C ... 25 °C / -20 °C ... 40 °C
Charge:.....	15 °C ... 30 °C / 0 °C ... 45 °C
Fast Charge:.....	15 °C ... 30 °C / 0 °C ... 40 °C
Discharge:.....	0 °C ... 40 °C / 0 °C ... 50 °C

No publication or circulation of data to third parties without consent of VARTA Consumer Batteries